


## MX Series Fixed Velocity Thickness Gauges



The **MX-1** and **MX-2** are fixed velocity gauges making them affordable precision tools that require no special training to operate.

The **MX-1** will hold a single velocity, making it the perfect choice where one material is being tested day after day. With the preset velocity in the gauge, you simply turn on the gauge and you are ready to work. The velocity is set in the **MX-1** with a simple software program that is supplied with the unit.

The **MX-2** is ideal for the person that tests a few different materials regularly. The **MX-2** contains 8 velocities of common materials and velocities that the user can set using a simple software program.

The **MX-1** and **MX-2** are packaged in all metal cases, sealed with gaskets to protect them from harsh working environments. These gauges can go where you go, to do the work you do, saving you time and money, making fast accurate measurements.

Dakota Ultrasonics offers quality gauges that are reliable, innovative and competitively priced—all backed by the longest warranty in the business—5 full years.

# THE MX SERIES THICKNESS GAUGES

**DAKOTA ULTRASONICS'** rugged thickness gauge family has been designed and built to satisfy the roughest industry conditions. The features offered in the **MX Series** allow the user to select a quality tool that will meet or exceed their specific application needs. Our 5 year limited warranty indicates how we feel about the reliability and durability of the **MX Series**.

## S P E C I F I C A T I O N S

### Physical

**Weight:**

10 ounces (with batteries).

**Size:**

2.5 W x 4.5 H x 1.24 D inches  
(63.5 W x 114.3 H x 31.5 D mm).

**Operating Temperature:**

-20° to 120°F (-30° to 50°C).

**Case:**

Extruded aluminum body with nickel-plated aluminum end caps (gasket sealed).

### Keypad

Sealed membrane that is resistant to both water and petroleum products.

Four or five tactile-feedback keys.

### Transducer

Dual-element (transmit and receive).

1 to 10 MHz frequency range.

Locking quick disconnect LEMO connectors.

4 foot cable.

Custom transducers available for special applications.



### Power Source

Two 1.5V alkaline or 1.2V NiCad AA cells.

Typically operates for 200 hours on alkaline and 130 hours on NiCad.

Display flashes when battery is low. Unit turns off automatically when battery is too low to operate reliably.

### Display

Multi-function 4.5 digit liquid crystal display with 0.500 inch numerals, backlit for use in poor light conditions.

Backlight is selectable on/off/auto (illuminates only when taking a measurement).

Measurements displayed in inches, inches/microsecond, millimeters, and meters/second.

Bar graph indicates stability of reading.

### Software

Comes complete with cable and software to transfer the velocity to the gauge.

### Certification

Factory calibration traceable to national standards.

### Warranty (all MX units)

5 year limited.

### Measuring

**Range:**

Measures from 0.025 to 19.999 inches (0.63 to 500 millimeters).

Switch to select English or Metric units.

**Resolution:**

0.001 inch (0.01 millimeter)

**Velocity Range:**

0.0492 to .3937 in./μs.  
(1250 to 10,000 meters/second)

Four readings per second for single point measurements.

**Velocity Settings:**

The MX-1 has 1 custom velocity setting.

The MX-2 has 8 set velocities and 2 that are custom to the user's application. The set velocities are as follows:

- |                        |      |
|------------------------|------|
| 1. Steel 4340          | .233 |
| 2. Stainless Steel 303 | .223 |
| 3. Aluminum 2024       | .251 |
| 4. Cast Iron           | .179 |
| 5. Plexiglass          | .106 |
| 6. PVC                 | .094 |
| 7. Polystyrene         | .092 |
| 8. Polyurethane        | .070 |
| 9. Custom              |      |
| 10. Custom             |      |

A S O N A T E S T P L C G R O U P C O M P A N Y

Distributed by:

**RUSSELL NDE SYSTEMS INC.**

4909-75 Avenue  
Edmonton, Alberta  
T6B 2S3 Canada  
Telephone: 780-468-6800  
Toll Free: 1- 800-661-0127  
Facsimile: 780-462-9378  
E-mail: info@russelltech.com  
www.russelltech.com